

MATCH PAINT

ELASTOMERIC COATING FOR TENNIS COURTS



DESCRIPTION

MATCH PAINT is a balanced elastomeric coating based on styrene-acrylic copolymers, designed for application on tennis courts made of concrete or asphalt. The product exhibits excellent abrasion resistance and long-term durability in outdoor environments.

TECHNICAL CHARACTERISTICS – UNAPPLIED PRODUCT

Specific gravity	1375 ± 15 g/L - ISO 2811:1974
Theoretical dry residue	58 ± 1% by weight

TECHNICAL CHARACTERISTICS – APPLIED PRODUCT

Drying time @20°C, 60% RH – Touch dry	50–60 minutes
Drying – Through dry	1–2 hours
Complete curing	36–48 hours
Theoretical coverage (two coats)	4–5 m ² /L (depending on dilution)

SURFACE PREPARATION AND APPLICATION CYCLE

Ensure that the substrate is not fresh, damp, weak or chalking. The surface must be clean and free from oils, grease, efflorescence and dust. On concrete courts, it is recommended to apply a first coat of diluted clear primer. Apply two or three coats of MATCH PAINT (diluted). White lines must be made using the product diluted with 5% water.

APPLICATION

PRODUCT APPLICATION

Application by brush, roller or spray.

Dilution:	10–30% water (depending on substrate absorption)
Application temperature:	5–35°C
Tool cleaning:	Water

OVERCOATING

4–6 hours @20°C, 60% RH.

VOC INFORMATION

EU VOC limit value (2010) (Cat A/i): 140 g/L
Product ready for use contains: max 50 g/L

WARNINGS

- Store containers in a cool place above +5°C, away from direct sunlight and heat sources.
- Shelf life: 24 months.
- Apply between +5°C and +35°C.
- Do not apply on surfaces exposed to direct sunlight during application.
- Protect painted surfaces from direct weathering for one week after application.
- Diluted product must be kept tightly closed, away from heat or sunlight, and used within three days.
- Mixing with materials not specified in this technical sheet may alter product performance.



Date 15/10/2025

Str, Via Piero Gobetti, 8,
15057 Tortona AL
Tel. 0131 866312

info@btechitalia.eu
www.btechitalia.eu

MATCH PAINT

ELASTOMERIC COATING FOR TENNIS
COURTS



HEALTH AND SAFETY

Refer to the latest Safety Data Sheet for instructions on handling, storage and disposal. Do not release product or empty containers into the environment.

For PROFESSIONAL USE ONLY.

LEGAL NOTICE

The information and recommendations given above, although they correspond to our best experience, must in any case be considered purely indicative and must be confirmed by exhaustive practical applications. Therefore, before using the product, anyone who intends to make use of it must determine whether it is or is not suitable for the intended application and, in any case, assumes all responsibility that may arise from its use. Always refer to the latest updated version of the technical data sheet, available on the website btechitalia.eu.

Date 15/10/2025



Str, Via Piero Gobetti, 8,
15057 Tortona AL
Tel. 0131 866312

info@btechitalia.eu
www.btechitalia.eu