



ZS-75

HIGH-PERFORMANCE
METHACRYLATE COATING



DESCRIPTION

ZS-75 is a high-quality methacrylate-based protective and decorative coating. It provides excellent adhesion, durability and surface protection for a wide range of substrates, ensuring long-lasting performance.

FIELDS OF APPLICATION

- Concrete
- Industrial floors
- Masonry
- Cement-based substrates
- High-durability protective coatings
- Decorative finishes

PRODUCT DATAS

Base	Value
Catalysis ratio	Solvent-based methacrylate
Mix ratio	One-component
Composition	-
Appereance	Liquid
Specific weight	1.0 kg/L
Dry residual	30.0%
Dilution	Solvent (5-10%)
Pot Life	60 minutes

CONSUMPTION

Brush/roller: 0.07 L/m² (one coat)

Low-pressure airless system: 0.03 L/m² (one coat)

Consumption may vary depending on porosity, temperature, humidity and application method.

COLORS

Available colours:

- RAL shades

PACKAGING

ZS-75 is supplied in:

- 20.0 kg

APPLICATION

SUBSTRATE PREPARATION

The substrate must be perfectly clean, dry, cohesive and free from contaminants (dust, dirt, grease, oils, paints, efflorescence, moss, etc.).

Date 15/10/2025

ZS-75

HIGH-PERFORMANCE
METHACRYLATE COATING



PRODUCT APPLICATION

Apply ZS-75 using brush, roller or airless spray*. After preparing the substrate, apply the product uniformly in a single coat.

*For airless spraying, a low-pressure system is recommended.

PRODUCT PREPARATION

Ready-to-use one-component product. Mixing is not strictly necessary, but it is recommended to stir the content to ensure full homogenisation.

CLEANING EQUIPMENT

Clean all tools and equipment immediately after use with solvent.

STORAGE

Store in original, undamaged containers in a dry place, away from heat sources, between +5 °C and +25 °C for up to 12 months.

WARNINGS

- Solvent-based product;
- Flammable;
- Do not apply below +5 °C;
- Do not dilute with unsuitable solvents;
- Colour may vary depending on the RAL shade selected;
- Do not apply in strong wind or rain.

HEALTH AND SAFETY

Refer to the latest Safety Data Sheet for instructions on handling, storage and disposal. Do not release product or empty containers into the environment.

For PROFESSIONAL USE ONLY.

LEGAL NOTICE

The information and recommendations given above, although they correspond to our best experience, must in any case be considered purely indicative and must be confirmed by exhaustive practical applications. Therefore, before using the product, anyone who intends to make use of it must determine whether it is or is not suitable for the intended application and, in any case, assumes all responsibility that may arise from its use. Always refer to the latest updated version of the technical data sheet, available on the website btechitalia.eu.



Date 15/10/2025

Str, Via Piero Gobetti, 8,
15057 Tortona AL
Tel. 0131 866312

info@btechitalia.eu
www.btechitalia.eu